

# F34<sup>®</sup> ALETHO ELITE

## SAE 0W-20 Full Synthetic Motor Oil

### API SN, ILSAC GF-5



#### PRODUCT DATA SHEET

#### PRODUCT DESCRIPTION

**F34<sup>®</sup> ALETHO ELITE SAE 0W-20 Full Synthetic Motor Oil API SN, ILSAC GF-5** is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged gasoline engines. This oil exceeds the performance requirements of API SN and ILSAC GF-5.

SAE J300 Viscosity Grade	0W-20
Appearance	Amber, Transparent Liquid
Viscosity @ 40°C, cSt, ASTM D445	44.55
Viscosity @ 100°C, cSt, ASTM D445	8.3
Viscosity Index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C
Flash Point, °C, ASTM D92	215
Pour Point, °C, ASTM D97	-48

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

#### Exceeds Performance Requirements

API SN with Resource Conserving, API SM, API SL, API SJ

ILSAC GF-5

Chrysler MS6395

Ford WSS-M2C947-A

**Product Code : F34100**



 **Latam Chemicals™**  
A Pochteca® Group Company

1 Riverway Dr. Ste. 17  
Houston, TX 77056  
+1 713 300 3900 | +1 832 560 4873  
ppickering@latamchemicals.com  
www.latamchemicals.com