

F34[®] ALETHO

SAE 10W-40, 20W-50 Synthetic Blend Motor Oil, API SN



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

F34[®] ALETHO SAE 10W-40, 20W-50 Synthetic Blend Motor Oil; API SN is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA C3.

SAE J300 Viscosity Grade	10W-40	20W-50
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	100.25	160.55
Viscosity @ 100°C, cSt, ASTM D445	14.5	18.5
Viscosity Index, ASTM D2270	150	130
CCS Apparent Viscosity, cP, ASTM D5293	5,600@-25°C	5,900@-15°C
MRV Apparent Viscosity, cP, ASTM D4684	21,000@-30°C	15,600@-20°C
Flash Point, °C, ASTM D92	215	220
Pour Point, °C, ASTM D97	-40	-30

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SN, API SM, API SL, API SJ

Product Code

SAE 10W-40 – F34107

SAE 20W-50 – F34108



 **Latam Chemicals[™]**
A Pochteca[®] Group Company

1 Riverway Dr. Ste. 17
Houston, TX 77056
+1 713 300 3900 | +1 832 560 4873
ppickering@latamchemicals.com
www.latamchemicals.com