

F34[®] ALETHO ELITE

SAE 5W-20, 5W-30 and 10W-30

Full Synthetic Motor Oil, API SN, ILSAC GF-5



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

F34[®] ALETHO ELITE SAE 5W-20, 5W-30 & 10W-30 Full Synthetic Motor Oil, API SN, ILSAC GF-5 are formulated with synthetic base oils and a premium additive package. These oils are designed for use in carbureted, fuel injected, turbocharged gasoline engines. These oils exceed the performance requirements of API SN and ILSAC GF-5.

SAE J300 Viscosity Grade	5W-20	5W-30	10W-30
Appearance, Visual	Amber, Transparent, Liquid		
Viscosity @ 40°C, cSt, ASTM D445	47.75	61.25	68.75
Viscosity @ 100°C, cSt, ASTM D445	8.3	10.8	10.9
Viscosity Index, ASTM D2270	150	170	150
CCS Apparent Viscosity, cP, ASTM D5293	4,800@-30°C	5,200@-30°C	4,900@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	15,000@-35°C	18,000@-35°C	9,000@-30°C
Flash Point, °C, ASTM D92	215	215	218
Pour Point, °C, ASTM D97	-44	-42	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API SN with Resource Conserving, API SM, API SL, API SJ

ILSAC GF-5

Chrysler MS6395

Ford WSS-M2C946-A (5W-30); Ford WSS-M2C945-A (5W-20)

Product Code

SAE 5W-20 – F34101

SAE 5W-30 – F34102

SAE 10W-30 – F34103



 **Latam Chemicals™**
A Pochteca® Group Company

1 Riverway Dr. Ste. 17
Houston, TX 77056
+1 713 300 3900 | +1 832 560 4873
ppickering@latamchemicals.com
www.latamchemicals.com