F34® DYO Two-Cycle Engine Oil

PRODUCT DATA SHEET



PRODUCT DESCRIPTION

F34® DYO Two-Cycle Engine Oil is a multi-purpose 2-stroke engine oil designed for use in air-cooled two-cycle engines such as motorcycles, lawn mowers, scooters, golf carts, chain saws, and other air-cooled two-stroke powered equipment. This product is formulated with group II paraffinic base oils and performance additive package designed for engine cleanliness to prevent ring sticking, spark plug fouling and reduce engine smoking.

TYPICAL PROPERTIES*				
Parameter	Result			
Appearance, Visual	Blue, Dyed, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	42.0			
Viscosity @ 100°C, cSt, ASTM D445	8.0			
Viscosity Index, ASTM D2270	166			
Flash Point, °C, ASTM D92	150			
Pour Point, °C, ASTM D97	-35			

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Fuel Mixing Ratio, Ounces of Oil to Gallons of Gasoline							
Gas Vol	1 Gal	2 Gal	3 Gal	4 Gal	5 Gal	6 Gal	
Gas : Oil	0z	0z	0z	0z	0z	0z	
16:01	8	16	24	32	40	48	
20:01	6	13	19	26	32	38	
24:01:00	5	11	16	21	27	32	
25:01:00	5	10	15	20	26	31	
40:01:00	3	6	10	13	16	19	
50:01:00	3	5	8	11	13	16	

Suitable for Use: APLTC Product Codes: F34699









1 Riverway Dr. Ste. 17 Houston, TX 77056 +1 713 300 3900 | +1 832 560 4873 ppickering@latamchemicals.com www.latamchemicals.com