

F34[®] ISCHYROS

Synthetic Blend Heavy-Duty Engine Oils,

SAE 15W-40 and 20W-50; API CI-4/SL, CI-4 Plus



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

F34[®] ISCHYROS Synthetic Blend Heavy-Duty Engine Oil, SAE 15W-40 & 20W-50, API CI-4/SL, CI-4 Plus is a parasyntetic crankcase lubricant for use in modern diesel engines. Formulated with a blend of synthetic and conventional base oils as well as a premium quality additive package, this oil exhibits excellent detergent, dispersant, anti-wear, anti-corrosion, anti-oxidant, and anti-foaming properties.

SAE J300 Viscosity Grade	15W-40	20W-50
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	103.4	154.75
Viscosity @ 100°C, cSt, ASTM D445	14.5	18.5
Viscosity Index, ASTM D2270	145	135
CCS Apparent Viscosity, cP, ASTM D5293	5,000@-20°C	7,000@-15°C
Flash Point, °C, ASTM D92	220	235
Pour Point, °C, ASTM D97	-35	-30
Total Base Number, mg KOH/g, ASTM D2896	10	10

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Exceeds Performance Requirements

API CI-4 Plus, CI-4, CH-4, CF-4, CF-2, CF
API SL, SJ, SG, SF
ACEA E7
Cummins CES 20078

MB 228.1, 229.1
MAN 271
MTU Type 1
Volvo VDS-2

Mack EO-M Plus
Renault Truck RD/RD-2
CAT ECF-1-a
ZF TE-ML 07C

Product Code

SAE 15W-40 – F34210
SAE 20W-50 – F34211



 **Latam Chemicals™**
A Pochteca® Group Company

1 Riverway Dr. Ste. 17
Houston, TX 77056
+1 713 300 3900 | +1 832 560 4873
ppickering@latamchemicals.com
www.latamchemicals.com