

# F34<sup>®</sup> PROTOS ELITE EURO

## SAE 5W-30 Full Synthetic Motor Oil

ACEA C3-16, API SN



### PRODUCT DATA SHEET

#### PRODUCT DESCRIPTION

**F34<sup>®</sup> PROTOS Elite Euro SAE 5W-30 Full Synthetic Motor Oil ACEA C3-16, API SN** is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA C3.

SAE J300 Viscosity Grade	5W-30
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	68
Viscosity @ 100°C, cSt, ASTM D445	11.5
Viscosity Index, ASTM D2270	165
CCS Apparent Viscosity, cP, ASTM D5293	5,300@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-35°C
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-42
Sulfated Ash, wt%, ASTM D874	≤ 0.8

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

#### Exceeds Performance Requirements

API SN  
ACEA C3-16  
BMW LL-04  
MB 229.31/229.51  
GM dexos 2

#### Product Code

F34008



 **Latam Chemicals<sup>™</sup>**  
A Pochteca<sup>®</sup> Group Company

1 Riverway Dr. Ste. 17  
Houston, TX 77056  
+1 713 300 3900 | +1 832 560 4873  
ppickering@latamchemicals.com  
www.latamchemicals.com