

# F34<sup>®</sup> PROTOS ELITE

## SAE 0W-16 Full Synthetic Motor Oil

API SP, ILSAC GF-6B



### PRODUCT DATA SHEET

#### PRODUCT DESCRIPTION

**F34<sup>®</sup> PROTOS ELITE SAE 0W-16 Full Synthetic Motor Oil, API SP, ILSAC GF-6B** is a premium full synthetic motor oil manufactured for use in modern gasoline engines which require ILSAC GF-6B, API SP, API SN Plus, or API SN performance in the SAE 0W-16 viscosity grade.

**F34<sup>®</sup> PROTOS** products are formulated with synthetic base oils and premium performance additive packages which are specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

ISO VG	22	32	46	68
Appearance, Visual	Yellow, Transparent, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	22.0	32.0	46.0	68.0
Viscosity @ 100°C, cSt, ASTM D445	4.65	6.11	8.13	11.11
Viscosity Index, ASTM D2270	130	140	150	155
Flash Point, °C, ASTM D92	215	225	225	235
Pour Point, °C, ASTM D97	-45	-40	-40	-40

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

#### Suitable for Use:

- Parker Denison HF-0, HF-1, HF-2
- MAG IAS P-69 (ISO 68)
- MAG IAS P-68 (ISO 32)
- MAG IAS P-70 (ISO 46)
- GM LS-2
- JCMAS HK
- U.S. Steel 127
- U.S. Steel 136
- Bosch Rexroth RD90220
- SAE MS1004

#### Product Codes :

- ISO VG 22- SAE601
- ISO VG 32 - SAE602
- ISO VG 46 - SAE603
- ISO VG 68 - SAE604

#### Product Code

SAE 0W-16 - F34001



 **Latam Chemicals™**  
A Pochteca® Group Company

1 Riverway Dr. Ste. 17  
Houston, TX 77056  
+1 713 300 3900 | +1 832 560 4873  
ppickering@latamchemicals.com  
www.latamchemicals.com