

# F34<sup>®</sup> PROTOS ELITE

## SAE 5W-40 and 5W-50

### Full Synthetic Motor Oil, API SP



#### PRODUCT DATA SHEET

#### PRODUCT DESCRIPTION

**F34<sup>®</sup> PROTOS Elite SAE 5W-40 and 5W-50** are premium full synthetic motor oils manufactured for use in modern gasoline engines which require API SP or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

SAE J300 Viscosity Grade	5W-40	5W-50
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	86.8	115
Viscosity @ 100°C, cSt, ASTM D445	14.5	18.5
Viscosity Index, ASTM D2270	175	180
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-30°C	5,800@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-35°C	23,000@-35°C
Flash Point, °C, ASTM D92	215	215
Pour Point, °C, ASTM D97	-42	-42

\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

#### Exceeds Performance Requirements

API SP, API SN Plus, API SN

#### Product Code

**SAE 5W-40** - F34006

**SAE 5W-50** - F34007



 **Latam Chemicals<sup>™</sup>**  
A Pochteca<sup>®</sup> Group Company

1 Riverway Dr. Ste. 17  
Houston, TX 77056  
+1 713 300 3900 | +1 832 560 4873  
ppickering@latamchemicals.com  
www.latamchemicals.com