

F34[®] SKLIRA

Super Tractor Oil Universal

SAE 10W-30 & SAE 15W-40



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

F34[®] SKLIRA Super Tractor Oil Universal SAE 10W-30 and SAE 15W-40 are premium multi-purpose tractor lubricants designed for use in engines, transmissions, final drives and hydraulic systems of various off-road equipment. These multi-use fluids are formulated with group II paraffinic base stocks and a premium performance additive package which provides robust anti-wear, anti-oxidant, anti-foam, and detergent properties. Further, specialty friction modifiers minimize chatter, sticking or slipping for wet brakes and power take-off clutches. These -multi-grade fluids are designed for year-round performance in all seasons.

SAE J300 Viscosity Grade	10W-30	15W-40
Appearance, Visual	Amber, Transparent, Liquid	
Viscosity @ 40°C, cSt, ASTM D445	67.25	103.4
Viscosity @ 100°C, cSt, ASTM D445	10.5	14.5
Viscosity Index, ASTM D2270	145	145
CCS Apparent Viscosity, cP, ASTM D5293	5,500@-25°C	5,950@-20°C
Flash Point, °C, ASTM D92	21,000@-20°C	18,500@-15°C
Pour Point, °C, ASTM D97	215	225
Total Base Number, mg KOH/g, ASTM D2896	-35	-32

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Suitable for Use:

API CF-4, CF, CE, CD/SF
API GL-4
Massey Ferguson MF 1145, 1144
Massey Ferguson MF 1139 (10W-30)

John Deere J27C
ZF TE ML 06B, 07B
Ford M2C 159 B/C
Ford New Holland 82009201/2/3

Product Code

SAE 10W-30 – F34503
SAE 15W-40 – F34504



 **Latam Chemicals[™]**
A Pochteca[®] Group Company

1 Riverway Dr. Ste. 17
Houston, TX 77056
+1 713 300 3900 | +1 832 560 4873
ppickering@latamchemicals.com
www.latamchemicals.com