F34® YPSILOS ELITE MULTIPLEX

HVI AW Synthetic Hydraulic Oil ISO VG 22, 32, 46 & 68

PRODUCT DATA SHEET



PRODUCT DESCRIPTION

F34® YPSILOS ELITE MULTIPLEX HVI AW Hydraulic Oils are full synthetic, multi-grade, premium, multi-purpose hydraulic oils designed for use in severe applications as we I as applications which may experience wide temperature variance. Formulated with synthetic base stocks and highly shear-stable viscosity modifiers, these multi-grade oils provide consistent viscometrics across wide temperature ranges ensuring even power transmission of the hydraulic system across wide operating temperatures. The carefuly selected synthetic base stocks provide superior oxidation protection thus extending oil life. Further, these oils are fortified with an additive package that includes anti-wear, anti-oxidant, and anti-corrosion agents as we I as demulsifier and defoamer. Available in the ISO 22, 32, 46, and 68 viscosity grades, F34® YPSILOS ELITE MULTIPLEX HVI AW Hydraulic Oils are top tier synthetic hydraulic fluids recommended for the most demanding applications.

Typical Properties*

ISO VG	22	32	46	68
Appearance, Visual	Yellow, Transparent, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	22	32	46	68
Viscosity @ 100°C, cSt, ASTM D445	4.65	6.11	8.13	11.11
Viscosity Index, ASTM D2270	130	140	150	155
Flash Point, °C, ASTM D92	215	225	225	235
Pour Point, °C, ASTM D97	-45	-40	-40	-40

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Suitable for Use:

SAE MS1004

Parker Denison HF-0, HF-1, HF-2 MAG IAS P-69 (ISO 68) MAG IAS P-68 (ISO 32) MAG IAS P-70 (ISO 46) GM LS-2 JCMAS HK U.S. Steel 127 U.S. Steel 136 Bosch Rexroth RD90220

Product Code:

ISO VG 22- F34601 ISO VG 32 - F34602 ISO VG 46 - F34603 ISO VG 68 - F34604







1 Riverway Dr. Ste. 17 Houston, TX 77056 +1713 300 3900 | +1832 560 4873 ppickering@latamchemicals.com www.latamchemicals.com